


Tramway switch with replaceable flexible blades



Pražská strojirna a.s.



+420 284 810 852



info@pstroj.cz



www.pstroj.cz

Tramway block switches are made for right and left branching and can be used as trailing or facing. They are constructed for use in the most demanding conditions of tramway tracks.

They guarantee a high degree of passage safety, quiet function, are ecologically harmless and feature a long lifetime with minimum demands for maintenance.

Securing:

- in cooperation with the facing or trailing direction setting system, an automated or manual resetting of the switch blades into the required direction and thus a safe tramway train passage in the straight or branching direction,
- the switch construction enables the use of modern, unified setting devices with the setting and checking rod.

Pražská strojirna a.s.

Tramway switch with replaceable flexible blades




Description:

The switch is made of grooved rails required by the customer (NT1, 60R2, 60R1, 59R2, 59R1 ...). Each switch consists of two half switches set to the required gauge using spacers. The half switch frames are made as weldments and are welded to the base plate along their entire length. The upper frames form sliding surfaces for the tongues. Both switch tongues (curved and straight) are replaceable – they are each fastened with four M20x1.5 screws for replacement and the position of the tongues is secured by a tongue-and-groove joint, the screw heads are secured against spontaneous loosening. The flexible elastic parts of the tongues are made of rail materials or wear-resistant steels. Both half-exchanges are heated by heaters that are screwed to the side of the exchange, are replaceable, and are housed in a stainless steel protector for easy replacement.

Technical parameters:

Track gauge: according to the customer's needs (1435, 1000, 1067, 1524mm ...).
Rail profile: according to the customer's requirement (NT1, 60R2, 60R1, 59R2, 59R1 ...).
Branching radius: standard R 20, 25, 30, 50, 100 a 150m and or another, depending on the customer's needs.

	R = 20 m				R = 25 m		R = 30 m		R = 50 m				R = 100 m		R = 150 m	
Rail	60R2, 60R1, 59R2, 59R1		NT1		60R2, 60R1, 59R2, 59R1		60R2, 60R1, 59R2, 59R1		60R2, 60R1, 59R2, 59R1		NT1, NT3		60R2, 60R1, 59R2, 59R1, NT1		60R2, 60R1, 59R2, 59R1, NT1	
Gauge	1000	1435	1000	1435	1000	1435	1000	1435	1000	1435	1000	1435	1000	1435	1000	1435
L	4500	4500	3400	3400	4500	4500	4000	4000	5000	5000	4660	4660	7000	7000	8500	8500
v *	500	500	0	0	500	500	500	500	350	350	0	0	200	200	0	0
γ	11° 45' 11"	11° 53' 08"	9° 45' 18"	9° 45' 18"	9° 21' 16"	9° 26' 18"	7° 46' 06"	7° 49' 36"	5° 47' 14"	5° 48' 48"	5° 16' 25"	5° 16' 25"	4° 01' 51"	4° 02' 23"	3° 15' 27"	3° 15' 44"
	13,0589 g	13,2062 g	10,8390 g	10,8390 g	10,3938 g	10,4869 g	8,6322 g	8,8963 g	6,4305 g	6,4589 g	5,8595 g	5,8595 g	4,4787 g	4,4885 g	3,6196 g	3,6249 g
a	500	500	130	130	500	500	0	0	0	0	130	130	0	0	0	0
b	0	0	280	280	0	0	400	400	650	650	280	280	800	800	1000	1000
c	500	500	310	310	500	500	400	400	350	350	310	310	400	400	400	400
d	1000	1000	720	720	1000	1000	800	800	1000	1000	720	720	1200	1200	1400	1400
e	389	385	259	259	313	311	262	260	247	247	203	203	243	243	240	240
f	409	413	279	279	326	329	271	273	253	253	209	209	246	246	242	242
g	25	25	7	7	16	16	11	11	8	8	3	3	6	6	4,5	4,5
h	28	29	3	3	18	18	12	12	9	9	0	0	6	6	4,5	4,5
i	205	298	244	244	163	236	166	196	101	145	132	132	70	101	57	82
T	2059	2082	1707	1707	2045	2064	2037	2052	2527	2539	2303	2303	3519	3527	4255	4272
v *	is only in case of using electric heating according VDV															



Pražská strojirna a.s.



+420 284 810 852



info@pstroj.cz



www.pstroj.cz

Pražská strojirna a.s.